

1000m fiber optic cable paired with a 100Mbps switch



1000m fiber optic cable paired with a 100Mbps switch



Easy to Install and Compact Design PLUG & PLAY - Simply plug in Single SC optical port and UTP port, and it will work right away. The measurement is 9.3 cm x 7.1cm x 2.7cm (0.3"x 0.2"x 0.1"), which gives you flexible installation options.



The GSD-1002M supports dual-speed, 100Base-FX and 1000Base-SX/LX SFP (Small Form-factor Pluggable) fiber-optic modules to connect fiber access point, ...



The units have been designed to automatically detect a 10 Mbps, 100 Mbps or 1,000 Mbps ethernet data rate. Units are available for both Multi-Mode and Single-Mode fiber optic cables with transmission ...




Our 1000BASE-T Copper SFP module delivers dedicated Gigabit Ethernet connectivity over existing copper cabling. Supporting 1000 Mbps data rates over distances up to 100m using Cat5e or better ...



These modules allow switches or routers designed for optical transceivers to connect directly to twisted-pair copper networks while maintaining support for 10Mbps, 100Mbps, and 1Gbps Ethernet speeds.



Using D-Link's converters you can change a twisted-pair Ethernet connection into a single-mode or multi-mode fiber connection which can support for distances from 550 m to 20 km.



Buy Gigabit fiber media converter designed to convert single mode, multimode of 10, 100 and 1000 Base fiber optic cable. This gigabit media converters support 10/100/1000Mbps transmission speeds over ...



10GBase media converter supports a 10GbE fiber connection with CAT.6a, CAT7 RJ45 Copper. This converter designed with 2 SFP+ slots, SFP1 port for a SFP+ -T module, SFP2 port for a SFP+ fiber ...



Supporting a maximum multimode fiber-optic cable distance of 550 meters (0.34 miles), the media converter delivers a simple and reliable solution for connecting ...




Supporting a maximum multimode fiber-optic cable distance of 550 meters (0.34 miles), the media converter delivers a simple and reliable solution for connecting Gigabit Ethernet networks to remote ...



The S-1110 SFP Media and Rate Converter transparently connects copper to SFP for multimode or single mode fiber. It also automatically detects if the copper port speed is 10Mbps, 100Mbps, or 1G ...




Our 1000BASE-T Copper SFP module delivers dedicated Gigabit ...



The information in this guide about hardware platform support is current as of the date this guide was published. Support for specific SFP types might have been added to other switches or I/O modules ...



The B1-POE33026PFM is a gigabit L2+ managed PoE fiber switch independently developed by BISMUN. It has 24*10/100/1000Base-T adaptive RJ45 ports and 4*100/1000Base-X uplink SFP fiber ...



Use a straight-through patch cable, such as a CAT5/CAT6 10/100/1000BaseT unshielded twisted pair (UTP) patch cable, when you connect a PC, server, printer, or other end-user devices ...

Contact Us

For more information, pricing, or custom data center solutions, please contact us:

Website: <https://yoahorroenergia.es>

Email: hello@yoahorroenergia.es

Phone: +233 54 318 7269

Address: Plot 28, Spintex Road, Accra, Greater Accra, Ghana

This document is for informational purposes only. Specifications subject to change without notice.

