





## Haiti-branded 25G optical core router

### Ordering information


NO.	1	2	3	4
Model	FS4M1	FS8M2	FS12M3	FS16M4
Product name	Patch Panel	Patch Panel	Patch Panel	Patch Panel
Illustration				
HU	1	2	3	4
Maximum number of cores	96	192	288	384
Product size (excluding modules and adapters)	482.6*208.7*43.7mm	482.6*208.7*88.1mm	482.6*208.7*132.5mm	482.6*208.7*177.7mm
Standard color code	RAL9005	RAL9005	RAL9005	RAL9005



## Haiti-branded 25G optical core router



I decided to not build a router anymore, but instead build a server that happens to be a router. In practice, this means that the bare metal is running Proxmox as a hypervisor, and one of the ...



The Cisco ® 25GBASE SFP28 (Small Form-Factor Pluggable) portfolio offers customers a wide variety of high-density and low-power 25 Gigabit Ethernet connectivity options for data center and high ...



Meet the new generation of 25G PON fiber broadband solutions. Our 25G PON optical modems are designed for multi-Gigabit connectivity to any end point: homes, enterprises, or mobile cell sites.



Tax included. This item is a deferred, subscription, or recurring purchase. By continuing, I agree to the and authorize you to charge my payment method at the prices, frequency and dates listed on this ...



The SFP28 25G SR optical module, a core component of 25G Ethernet, offers high performance, low power consumption, and high port density. It is widely used in data centers, enterprise networks, and ...



Optcore 25G SFP28 transceiver is a speed-enhanced variation of the SFP+ module. This transceiver is ideal for 25G Ethernet, telecom, and data center. We offer a comprehensive line of 25G transceivers, ...



As 25G Ethernet becomes a key building block for modern data centers and enterprise networks, the SFP28 25G LR transceiver has emerged as a reliable solution for long-reach, high-speed optical ...



A practical guide to selecting and implementing 25G optical modules, based on network needs and equipment compatibility.



The S9701-82DC is a high density 25G open and disaggregated router capable of deploying a pay as you grow routing cluster at the edge and core network.



SFP28 optical transceiver modules provide a transmission rate of 25 Gbps and use LC connectors. 25G BiDi transceivers always require paired sets: a -U must pair to a -D on the opposite end of the BiDi ...

## Contact Us

For more information, pricing, or custom data center solutions, please contact us:

Website: <https://yoahorroenergia.es>

Email: [hello@yoahorroenergia.es](mailto:hello@yoahorroenergia.es)

Phone: +233 54 318 7269

Address: Plot 28, Spintex Road, Accra, Greater Accra, Ghana

This document is for informational purposes only. Specifications subject to change without notice.

