

How to turn off the optical port on a Huawei switch



Overview

Execute the command “combo enable fiber” in interface mode to switch to the optical interface; on the contrary, “undo combo enable fiber” switches to the default electrical interface state. Enter system view, return user view with return command. If an interface is not connected to a cable or a fiber, disable the interface using the shutdown command to prevent exceptions caused by.

Page 5 S5700-52X-LI-AC • 48 10/100/1000Base-T Ethernet ports, 4 10GE SFP+ ports (10GE/GE auto-sensing) • Two models: AC model and DC model, supporting S5700-52X-LI-DC RPS (redundant power supply) • Forwarding performance:132 Mpps • 48 10/100/1000Base-T Ethernet ports, 4 10GE SFP+ ports. Problem: All optical ports cannot be connected, and the indicator lights are not on. Solution: To solve this problem, you can follow these steps: Check if the fiber and optical modules are compatible. Perform a. The undo am isolate command cancels unidirectional isolation between the current interface and a specified interface. For example: Replace USERNAME with the new username, set the password, define service-type (telnet, ssh, etc.

How to turn off the optical port on a Huawei switch




This article summarizes several solutions for using optical modules with switches and common problems encountered during usage, along with specific solutions.



Note: By default, the optical interface of the Combo interface is in the disabled state; use the above command to switch to the optical interface mode, and the accessed GE SFP module can ...



After modifying parameters of an interface, run the shutdown and undo shutdown commands, or run the restart command to make the modification take effect. If an interface is not connected to a cable or a ...



This text is a guide detailing Basic Command Line Interface (CLI) Commands on Huawei brand switches. It provides step-by-step instructions for users to perform fundamental network configuration ...



After port isolation is configured, ports are isolated at Layer 2 but can communicate at Layer 3 by default. To configure both Layer 2 isolation and Layer 3 isolation, run the port-isolate mode all ...



The main difference between trunk and hybrid is that hybrid port can allow multiple VLAN packets to be untagged, while trunk port only allows default VLAN packets to be untagged, and hybrid and trunk ...



Huawei battery LAN switches solve this problem. The use of internal batteries ensures stable operation of the access layer in the event of power failures.



H3C switch commands bear resemblance to Huawei switch commands but with subtle differences. Let's first understand the configuration commands and functions of H3C.



The port color change from orange to yellow when you create a VLAN configuration on a Cisco edge switch after migrating to a Huawei backbone switch is likely due to a mismatch in the ...

Contact Us

For more information, pricing, or custom data center solutions, please contact us:

Website: <https://yoahorroenergia.es>

Email: hello@yoahorroenergia.es

Phone: +233 54 318 7269

Address: Plot 28, Spintex Road, Accra, Greater Accra, Ghana

This document is for informational purposes only. Specifications subject to change without notice.

