

Huijue 80km 50g Optical Module



Huijue 80km 50g Optical Module



This module contains 2-lane optical transmitter, 2-lane optical receiver and module management block including 2 wire serial interfaces. The optical signals are multiplexed to a single-mode fiber through ...



50G QSFP28 ZR2 LWDM optical module is designed for use in 50G Ethernet links reach up to 80km over single-mode fiber via a Duplex LC connector - AscentOptics.



Q282D080500F is a high performance QSFP28 transceiver module for 50Gbps data links over a single mode fibre pair. The maximum reach is 80km. The two transmitters are cooled 1310nm LAN-WDM ...



50GBASE-ZR2 QSFP28 is a high-performance transceiver that supports up to ...



50G QSFP28 ZR2 LWDM optical module is designed for use in 50G Ethernet links reach up to 80km over single-mode fiber via a Duplex LC connector - AscentOptics.



Engineered with precision, this QSFP28 module operates at a wavelength of 1311nm, supports a 50G data rate, and facilitates two-fiber bidirectional communication over distances of up to 80km.



The 50GBASE-ZR2 QSFP28 Optical Transceiver Module is a high performance transceiver that supports up to 80km link lengths over OS2 SMF. Digital Diagnostics functions are available via a 2 ...



50GBASE-ZR2 QSFP28 is a high-performance transceiver that supports up to 80km link lengths over OS2 SMF. The maximum reach is 80km. The two transmitters are cooled 1310nm LAN-WDM lasers ...




50GBASE-ZR2 QSFP28 is a high-performance transceiver that supports up to 80km link lengths over OS2 SMF. The maximum reach is 80km. The two transmitters are cooled 1310nm LAN-WDM lasers ...



When this type of optical module is used to interconnect with a WDM device, the 1+1 protection switching duration on the client side of the WDM device is longer than 50 ms. The optical power ...



LNK-OM9380ZS100 is designed for 80 km optical communication applications. This module contains 2-lane optical transmitter, 2-lane optical receiver and module management block including 2 wire ...



This module contains 2-lanes optical transmitter, 2-lanes optical receiver and module management block including 2 wire serial interface. The optical signals are multiplexed to a single-mode fiber through ...



50GBASE-ZR2 QSFP28 is a high performance transceiver that supports up to 80km link lengths over OS2 SMF. Digital Diagnostics functions are available via a 2-wire serial interface.

Contact Us

For more information, pricing, or custom data center solutions, please contact us:

Website: <https://yoahorroenergia.es>

Email: hello@yoahorroenergia.es

Phone: +233 54 318 7269

Address: Plot 28, Spintex Road, Accra, Greater Accra, Ghana

This document is for informational purposes only. Specifications subject to change without notice.

