

Zambia CFP2100G



Zambia CFP2100G



CFP2100G(2V100Ah) Charged Volume Charge Voltage Charging Current Effect of Temperature on Capacity




100G CFP2 LR4/OTU4, 1310nm, 10km, DDM, LC/UPC Duplex, Single Mode, Optical Transceiver Module Specs 103.125 Gbps 10km 1310 nm LC/UPC Duplex P/N: MJ-CFP2100G-LR4 SKU: 1113102 ...



The Generic compatible CFP2 optical transceiver module is designed for use in 100 Gigabit Ethernet links over 10 km of single-mode fiber and complies with the CFP MSA CFP2 Hardware Specification ...



100GBASE-LR4 and OTN CFP2 Transceiver Module (SMF, 1310nm, 10km, LC, DOM) SPECIFICATION



It works to interconnect equipment with CFP2 model optical interfaces/ports to ...



CFP2100G (2V100Ah) Dimensions The Relationship for Open Circuit Voltage and Residual Capacity (25°C)



©2019 Jabil Inc. JABIL and the Jabil logo are registered trademarks of Jabil, Inc. and/or its subsidiaries in the United States and certain other countries. Other trademarks and product names may be the ...




This product has acquired the relevant product qualification (s)/license (s) of certain applicable country/countries. View more.



Designed to transmit and receive data in both directions on a single fiber for 100G and beyond. Provides an operationally efficient and cost-effective way for telecommunications and cable operators to ...



It works to interconnect equipment with CFP2 model optical interfaces/ports to exchange and transmit data of up to 100Gbps over 10km. Through an optical cable or cord using 2 fibers, you will be able to ...



Note: The MSA recommends host termination resistor value of 560 Ohms, which provides the best balance of performance for both open-drain and active tri-state driver in the module.

Contact Us

For more information, pricing, or custom data center solutions, please contact us:

Website: <https://yoahorroenergia.es>

Email: hello@yoahorroenergia.es

Phone: +233 54 318 7269

Address: Plot 28, Spintex Road, Accra, Greater Accra, Ghana

This document is for informational purposes only. Specifications subject to change without notice.

